

Adhesive Tapes

VaporBond Tape (TVB4)



This white single-sided tape combines a heavy-duty, weather-resistant polyethylene backing with an aggressive rubber adhesive. VaporBond Tape offers excellent seaming capabilities for our materials with an "Easy Tear" feature to reduce installation time. Typical applications include vapor retarders, covers and liners. Available in a 4" x 210' roll.

Butyl Seal Tape (TP2BR)



Butyl seal is a double-sided reinforced aggressive black butyl rubber tape used to join panels of polyethylene and polypropylene together by overlapping the edges and applying Butyl Seal in between. It is also used to adhere to concrete walls and footings when properly prepared. Butyl Seal is non-hardening and flexible. Available in 2" x 50' roll.

Properties:

	VaporBond Tape (TVB4)	Butyl Seal Tape (TP2BR)
Backing	7.5 mil Polyethylene	Coated Release Paper
Adhesive	1.5 mil Rubber Based Pressure-Sensitive	1 mm Black Butyl Rubber
Color	White	Black
Type	Single Sided	Double Sided
Size	4" x 210'	2" x 50'
Rolls Per Case	12	20
Weight Per Case	45 lbs	55 lbs
Adhesion Values	30 oz./ in. (to steel)	107.5 oz./ in. (to steel)
Service Temp.	-40° F to +180° F	30° F to +100° F
Minimum Application Temp.	50° F	35° F
Ideal Storage Temp./Humidity	70° F w/ 40-50%	70° F w/ 40-50%